

GXW-410x FXO Analog Gateway



The **GXW-410x** is a next generation IP voice & video gateway that features full interoperability with leading IP-PBXs, SoftSwitches and SIP server platforms. The gateway series includes the GXW4104 (4-port) and GXW4108 (8-port) model, each offering superb voice and video quality, traditional PBX telephone functionality, and easy deployment. The GXW410x is the only small business gateway that offers a video surveillance component in the industry. The video surveillance port enables after-hours security monitoring.

Features

- 4-and 8-FXO-port media gateways
- Video surveillance port
- Two RJ-45 ports (switched or routed)
- Supports PSTN/PBX analog trunk lines and SIP trunk interface
- Multiple SIP accounts and profiles (3 per system)
- Audio Codecs: G.711, G.723, G7.29, GSM, G.726, G.168
- Real time H.264 video codec (CIF resolution, up to 30fps)
- T.38 Fax

Benefits

- Interconnect remote location legacy phone lines across the Internet
- Web management for easy configuration and installation
- Provides fax, voice, video surveillance, and modem support
- Video surveillance port to enhance premise security.
- Can be a stand-alone gateway for IP Communications

Grandstream Networks, Inc. www.grandstream.com

Boston, Massachusetts
1297 Beacon Street, 2F
Brookline, MA 02446
1-617-566-9300

Dallas, Texas
2828 W.Parker Rd, Suite 102
Plano, TX 78075
1-469-241-0100

Los Angeles, California
1301 John Reed Ct.
City of Industry, CA 91745
1-626-956-0260

Shenzhen, China 518057
Bldg#1, No.2 Kefa Rd
Science & Technology Park
86-755-26014600

GXW-410x

Technical Specifications

	GXW-4104	GXW-4108
Interfaces		
Voice Ports	4 ports	8 ports
Telephone Interface	FXO, RJ11	
Network Interface	10/100 BASE-TX, RJ45	
LED Indicators	Power, Video, Network, and Line LEDs	
On/Off Switch	Yes	
Voice, Fax, Modem, Video Surveillance		
Voice over Packet Capabilities	G.168 Line Echo Cancellation, Dynamic Jitter Buffer, Modem detection & auto-switch to G.711	
Voice Compression	G.711, G.723, G.729A/B, GSM, G.726 (pending)	
Video Surveillance	real-time base line H.264 (CIF resolution, up to 30fps)	
DHCP Client/Server	Yes, NAT Router or Switched Mode	
Fax over IP	T.38 compliant Group 3 Fax Relay up to 14.4kbps and auto-switch to G.711 for Fax Pass-through (pending)	
QoS	Diffserve, TOS, 802.1 P/Q VLAN tagging	
IP Transport	RTP/RTCP & PPPoE	
Signaling		
PSTN Signaling	FXO Loop start	
DTMF Method	flexible DTMF transmission method, User interface of In-audio, RFC2833, and SIP Info	
IP Signaling	SIP (RFC 3261)	
Multiple Accounts Per Box	Up to three(3) distinct SIP accounts	
Provisioning	TFTP and HTTP; Round-robin port scheduling to ensure available lines to access PSTN	
Security		
Media	SRTP (pending)	
Control	TLS/SIPS (pending)	
Management	Syslog support, HTTPS and telnet (pending), remote management using Web browser	
Physical		
Power	12VDC - 100 -240 VAC/ 50-60 Hz	
Environmental	1.Operational: 40-130°F/5-45°C / 2.Storage: 10-130°F/0-40°C / 3.Humidity: 10 -90% Non-condensing	
Dimensions (HxWxD)	42 x 172 x 225 mm	
Mounting	Rack mount, Wall mount, Desktop	
Additional Features		
Caller ID	Bellcore Type 1 & 2, ETSI, BT, NTT, and DTMF-based CID	
Polarity Reversal / Wink	Yes	
Homologation		
EMC	FCC Part 68 & Part 15B, CE (EN55022, EN55024)	
Safety	UL	

