



BDCOM

BDCOM GP3600 Series High-density Rack-mounted GPON OLT

BDCOM GP3600 Series

Product Overview

BDCOM GP3600 complies with ITU-T G.984/G.988 and meets requirements about GPON OLT in *Network Access Technical Requirements*. It fully supports CTC2.0, automatic discovery and cooperation with ONUs of different manufacturers.

BDCOM GP3600 supports the Asymmetric uplink 1.25Gbps/downlink 2.5Gbps PON transmission rate, efficient bandwidth usage and Ethernet services, helping carriers to provide reliable services to their users.

Its coupling ratio ups to 1:128, and its support of different hybrid ONU networks minimize the carrier's investment.

BDCOM GP3600, based on the edge-cutting technologies, is strong in functions. A few of its functions such as QoS guarantee, SLA and DBA can be easily listed out.



GP3600-08



GP3600-16

Product Characteristics

- **GPON:** Abiding by ITU-T G.984/G.988, BDCOM GP3600 series OLT meets relevant requirements of GPON OLT regulated in *Network Access Technical Requirements* and China Telecom GPON Technical Requirements CTC2.0;
- **System Capacity:** GP3600 Series supports 8/16 GPON ports.
- **Uplink Interface:** GP3600 Series is equipped with 4 gigabit SFP ports, 4 gigabit combo ports and 4 10GE SFP+ ports.
- **Dimensions:** 1U, occupies a small space.
- **Environmental Protection:** low power consumption and low operating cost.
- **Bus Optical Fiber Protection:** the link can be automatically switched when trouble occurs in the optical fiber;

- Power Characteristics:** supports dual-AC, dual-DC and AC/DC power supply. The power supply supports modularized design, hot-swap and EMC-3 standard. It well adapts to the environment.

Technical Parameters

Attributes		GP3600-08	GP3600-16
System Capacity		Maximum coupling ratio:1:128 Backplane bandwidth:205G MAC table capacity: 64K	
Interface	PON	8	16
	Uplink interface	8 GE ports (4 gigabit SFP ports, 4 gigabit TX/SFP combo ports) 4 10GE SFP+ ports	
Attributes of the PON Interface		The transmission rate with downlink 2.5Gbps/uplink 1.25Gbps Class B ⁺ and Class C ⁺ GPON module Security: ONU authentication mechanism	
Standards		ITU-T G.984/G.988 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IEEE 802.1w, RSTP IEEE 802.3ad physical link static/dynamic aggregation (LACP) Ethernet – II	
QoS		Backpressure flow control (half duplex) IEEE 802.3x flow control (full duplex) IEEE 802.1p, CoS WRR, SP and FIFO queue schedule Limiting the uplink/downlink rate based on each ONU DBA and SLA	
VLAN		Port-based VLAN, 4K VLAN QinQ and flexible QinQ	

Multicast	<p>L2 Multicast</p> <p>IGMP Snooping</p> <p>MLD Snooping</p>
Reliability	<p>Unidirectional Link Detection (UDLD)</p> <p>Hot swap of the GPON optical module</p> <p>Optical path protection of GPON (type B/C, hand-in-hand)</p> <p>Abnormal luminescence ONU detection such as long luminescence</p>
Network Security	<p>Limiting the maximum number of users on each port</p> <p>Port isolation</p> <p>Packet storm control</p> <p>Flow-based ACL access control function</p> <p>Transmission data encryption on the PON interface</p>
Configuration Management	<p>Various management modes such as CLI, SNMP and TELNET</p> <p>Conducting software upgrade through TFTP</p> <p>Debug output</p>
Physical Characteristics	Dimensions mm (W×D×H): 442.5x304x 44
	Installation: standard 19-inch rack-mounted
	Weight:5.25Kg
Environment	Operating environment: 0°C-45°C; 10%-85% non-condensing
	Storage environment: -40°C-80°C; 5%-95% non-condensing
Power Supply	<p>Input voltage: AC90 ~ 240V, DC 36 ~ 72V</p> <p>dual-power input, DC/AC power supply and hot-swap</p>

Ordering Information

Model	Description
BDCOM GP3600-08	GPON OLT with 8 PON ports (1 console port, 1 out-band 10/100M port, 8 fixed PON ports (excluding the OLT SFP module), 4 gigabit SFP ports, 4 gigabit combo TX/SFP ports, 4 10G SFP+ ports; standard AC90~240V single power supply, expanded dual power supply, 19-inch rack-mounted installation)
BDCOM GP3600-08-DC	GPON OLT with 8 PON ports (1 console port, 1 out-band 10/100M port, 8 fixed PON ports (excluding the OLT SFP module), 4 gigabit SFP ports, 4 gigabit combo TX/SFP ports, 4 10G SFP+ ports; standard DC36V~72V, expanded dual power supply, 19-inch rack-mounted installation)
BDCOM GP3600-16	GPON OLT with 16 PON ports (1 console port, 1 out-band 10/100M port, 16 fixed PON ports (excluding the OLT SFP module), 4 gigabit SFP ports, 4 gigabit combo ports, 4 10G SFP+ ports; standard AC90~240V single power supply, expanded dual power supply, 19-inch rack-mounted installation)
BDCOM GP3600-16-DC	GPON OLT with 16 PON ports (1 console port, 1 out-band 10/100M port, 16 fixed PON ports (excluding the OLT SFP module), 4 gigabit SFP ports, 4 gigabit TX/SFP combo ports, 4 10G SFP+ ports; standard DC36V~72V single power supply, expanded dual power supply, 19-inch standard rack-mounted installation)
PWR-150-DC	OLT DC power supply (input voltage DC36V~72V, 150W max power)
PWR-150-AC	OLT AC power supply (input voltage AC90~240v, 150W max power)
OLT-GSFP-B+	OLT SFP module, Class B+ standard, downlink 2.5G/uplink 1.25G, TX wavelength 1490nm, RX wavelength 1310nm, SC interface
OLT-GSFP-C+	OLT SFP module, Class C+ standard, downlink 2.5G/uplink 1.25G, TX wavelength 1490nm, RX wavelength 1310nm, SC interface

For More Information

For more information about the **BDCOM P3600-16 Series**,
please contact your local BDCOM account representative.



Shanghai Baud Data Communication Co., LTD.

No.123, Juli Road,
Pudong Zhangjiang High-Tech Park,
Shanghai 201203, P.R.China

www.bdcom.cn

Tel: +86-21-50800666

Copyright ©Shanghai Baud Data Communication Co., LTD. 2016. All Rights Reserved.

This document is BDCOM Public Information.

BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time without notice.