

RADWIN JET, JET AIR Model

Sector Base Station - Data Sheet (RW5000/HBS-Air/5AC5/F54/UNI/JET/INT)



RW-5AC5-9654

Product Description

RW-5AC5-9654 is an AIR series beamforming sector Base Station radio unit (HBS). It provides 500 Mbps net aggregate throughput while delivering access connectivity for up to 64 Subscriber Units (HSU).

RW-5AC5-9654 supports 4.9 to 5.9 GHz and complies with Universal, MII, FCC, FCC/IC & UBR regulations.

The radio comes with a smart beamforming integrated antenna with embedded GPS.

Product Highlights

- Base station with smart beamforming antenna
- Up to 500 Mbps net aggregated throughput
- Long range - Up to 40 km / 25 miles
- Supports up to 64 HSUs
- Best Effort Service
- Dynamic channel bandwidth selection: 20/40/80MHz
- Short and constant latency
- Single radio supporting multiple bands
- Advanced MIMO, OFDM and Diversity technologies
- Robust and reliable operation in harsh conditions, extreme temperatures and non-line-of-sight scenarios
- Ease of operation and maintenance

Product Specifications:

Configuration					
Architecture	Outdoor Unit with a smart beamforming integrated antenna with embedded GPS				
PoE to ODU Interface	Outdoor CAT-5e; Maximum cable length: 100m for 10/100BaseT and 75m for 1000BaseT				
Radio					
Max Capacity	500 Mbps net aggregate throughput				
Subscriber Units support	Up to 64 subscriber units				
Channel Bandwidth	Configurable: 10, 20, 40, 80 MHz (for the default band)				
Modulation	MIMO-OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)				
Adaptive Modulation & Coding	Supported				
Smart Bandwidth Management (DBA)	Supported				
DFS	Supported (FCC)				
Diversity	Supported				
Max Tx Power	25 dBm				
Duplex Technology	TDD				
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6				
Encryption	AES 128				
Support Indoor units	RADWIN PoE devices (RW-9921-101X)				
Uplink / Downlink Allocation	Configurable: Symmetric or Asymmetric				
End to End Latency	Typical: 3.5msec @ 2 SUs; 20msec @ 64 HSUs				
Layer 2	Bridging learning of 5K MAC addresses				
QoS	Packet classification to 4 priority queues according to 802.1P or Diffserv				
VLAN Support	802.1Q, QinQ, 4094 VLANs				
TDD Intra Site Synchronization	Supported				
ODU Management	IPv4/IPv6 dual-stack; SNMPv1, SNMPv3; HTTP/HTTPS using web browser				
Supported Bands					
Band	CBW 10MHz [GHz]	CBW 20MHz [GHz]	CBW 40MHz [GHz]	CBW 80MHz [GHz]	Radio Compliance
5.1 GHz Universal	5.145-5.340	5.140-5.345	5.130-5.355	5.130-5.375	Universal
5.8 GHz MII	-	5.725-5.850	5.725-5.850	5.725-5.850	CMIIT RTA
5.9 GHz Universal	5.725-5.850	5.725-5.850	5.725-5.850	5.725-5.850	Universal
5.4 GHz FCC	-	5.480-5.715	5.480-5.715	5.485-5.715	FCC 47CFR Part 15.407
5.2 GHz FCC	-	5.255-5.340	5.255-5.340	5.250-5.340	FCC 47CFR Part 15.407
5.8 GHz FCC/IC	5.730-5.845	5.730-5.845	5.730-5.845	5.730-5.845	FCC 47CFR Part 15.407; ISSED RSS-247
5.4 GHz Universal (default)	5.470-5.725	5.465-5.730	5.455-5.740	5.455-5.760	Universal
4.9 GHz FCC/IC	4.940-4.990	4.940-4.990	-	-	FCC 47CFR Part 90 Subpart Y; IC RSS-111
4.9 GHz Universal	4.900-4.995	4.900-4.995	4.900-4.995	4.900-4.995	Universal
5.9 GHz Universal	5.725-5.955	5.720-5.960	5.710-5.970	5.710-5.990	Universal
5.1 GHz UBR	5.125-5.880	5.125-5.880	5.125-5.880	5.125-5.880	Universal
Mechanical					
ODU Dimensions	35.6(w) x 22.5(h) x 9.4(d) cm				
ODU Weight	3.3 kg / 7.28 lbs				
Power					
Power Feeding	Power provided over ODU-IDU cable				
Power Consumption	<30W				
Environmental					
Operating Temperatures	-35°C to 60°C / -31°F to 140°F				
Humidity	100% condensing, IP67 (totally protected against dust and against immersion in water up to 1m)				
Safety					
US/CAN (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22				
CE/IEC	EN/IEC 60950-1, EN/IEC 60950-22				
EMC					
FCC	47 CFR, Part15, Subpart B, Class B				
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4				
CAN/CSA-CEI/IEC	CISPR 22-2010 Class B				

Integrated Antenna	
Gain	20 dBi
VSWR	2.0 : 1
3 dB Azimuth Beamwidth	90 Deg. (typ)
Polarization	Dual Linear (Vertical and Horizontal)
Sidelobes Level	-12 dB(typ)
Cross Polarization	-30dB (typ)
F/B Ratio	-25 dB
Port To Port Isolation	35 dB (typ)
Lightning Protection	DC Grounded

Ordering Info

Part Number: RW-5AC5-9654

Description: RADWIN JET AIR ODU, with a smart beamforming integrated antenna with embedded GPS, supporting multi frequency bands at 5.x GHz, factory default 5.4 GHz Universal.

Datasheet information can be changed by manufacturer without prior notice